

KTR 620 – dane techniczne

CLAMPEX® – KTR 620															
d x D [mm]	średnica wałku d _w [mm]	przenoszony moment obr. lub siła osiowa		wymiary [mm]					śruby zaciskające DIN EN ISO 4017 - 10.9 µcałkowite=0,10			otwory demontażowe		nacisk po- wierzchniowy na wale	masa [~kg]
		T [Nm]	F _{ax} [kN]	B	B ₁	B ₂	B ₃	d ₁	M	z liczba	T _A [Nm]	M ₁	z ₁	P _H [N/mm ²]	
90 x 155	65	5200	160												
	70	6000	171	45	38	34	4	114	M10	11	59	M10	2	219	3,40
	75	6900	184												
100 x 170	70	6600	189												
	75	7600	203	50	43,5	39	4,5	124	M10	14	59	M10	2	206	4,60
	80	8600	215												
110 x 185	80	10600	265												
	85	11900	280	57	49	43,5	5	136	M12	12	100	M12	2	212	6,20
	90	13300	296												
120 x 197	85	12700	299												
	90	14200	316	61	53	48	5	147	M12	14	100	M12	2	205	7,40
	95	15700	331												
125 x 215	90	14600	324												
	95	16000	337	61	53,5	48	5,5	158	M12	14	100	M12	2	215	9,30
	100	17500	350												
130 x 230	95	18600	392												
	100	20300	406	66,9	57,5	51	6,5	165	M14	12	160	M14	3	225	11,90
	110	23600	429												
140 x 230	100	20100	402												
	105	21700	413	67	58	51	6	172	M14	12	160	M14	3	205	11,00
	115	25150	437												
155 x 263	110	27400	498												
	115	29600	515	72	63	55	7,5	186	M14	14	160	M14	3	212	16,00
	125	32000	533												
165 x 290	120	41500	692												
	125	44300	709	78	68	61	7,5	198	M16	12	250	M16	2	223	22,30
	135	47200	726												
175 x 300	130	47600	732												
	135	50500	748	78	69	61	8	208	M16	14	250	M16	4	216	23,30
	140	53500	764												
185 x 320	140	66000	943												
	145	69900	964	95,5	85,5	77,5	8	222	M16	16	250	M16	4	201	33,40
	150	73500	980												
200 x 340	150	82000	1093												
	160	91000	1138	98	88	77,5	8	238	M16	16	250	M16	4	280	37
	165	102000	1236												
220 x 370	160	105000	1313												
	170	122000	1435	120	107,5	96,5	8,5	268	M20	15	480	M20	3	250	53
	180	138000	1533												
240 x 405	170	125000	1471												
	180	145000	1611	123,5	111	98	11	288	M20	16	480	M20	4	276	66
	200	182000	1820												
260 x 430	190	165000	1737												
	200	190000	1900	138	125,5	110,5	9,5	312	M20	16	480	M20	4	278	80
	220	238000	2164												
280 x 460	210	220000	2095												
	220	245000	2227	152,5	140	121	14	334	M20	18	480	M20	6	265	103
	240	300000	2500												
300 x 485	220	297000	2700												
	230	330000	2870	155	140	124	16	360	M24	16	840	M24	4	276	116
	250	399000	3192												
320 x 520	240	331000	2758												
	250	365000	2920	157	142	124	18	380	M24	18	840	M24	6	290	134
	270	437000	3237												
340 x 570	250	429000	3432												
	260	469000	3608	174	159	139	20	402	M24	18	840	M24	6	288	185
	280	556000	3971												
360 x 590	270	545000	4037												
	280	592000	4229	178	163	143	20	424	M24	20	840	M24	5	292	207
	290	694000	4786												

Na zamówienie inne rozmiary.

Pierścień wewnętrzny do rozmiaru 40x80 jest z nacięciem, pierścień zewnętrzny dla wszystkich rozmiarów jest fosfatyzowany.